



STAINLESS STEEL UPRIGHT FREEZER

TKSA-UFS1410

STANDARD FEATURES

Double doors

- ✓ Deep-freeze stability and fast recovery. Fan-assisted airflow with 100 mm all-round insulation minimizes heat gain and speeds pull-down/re-pull after doors openings, maintaining a consistent -22 to -10 °C holding range across all levels.
- ✓ Low-maintenance freezer cycle. Automatic defrost with controlled heaters (evaporator only) restores coil efficiency without manual intervention, while automatic condensate evaporation keeps operation clean and reduces downtime.
- ✓ HACCP-ready temperature control. Digital thermostat with display provides precise setpoints and clear, at-a-glance readings for logging; operators can fine-tune to product and workload, ensuring compliant storage.
- ✓ Sealing, security, and serviceability. Self-closing, lockable solid door limits frost ingress and protects stock; easily replaceable magnetic gaskets preserve the seal.
- ✓ Professional build and capacity. Food-safe AISI 304 stainless steel inside/out; GN 2/1 loading with 6 adjustable shelves and approx. 1410 L capacity in a 148 × 83 cm footprint (201 cm high) for high storage-per-m² in back-of-house layouts.



PRODUCT SPECIFICATIONS

Dimensions	148 x 83 x 201 cm/h
Temperature	-22 °C to -10 °C
Volume	1410 L
Rated current	4.0 A
Refrigerant/Mass	R290 / 125 g
Energy source	220 V / 50 Hz
Foaming agent	C5H10