



# STAINLESS STEEL UPRIGHT FREEZER

**TKSA-UFS650**

## STANDARD FEATURES

Single door

- ✓ Deep-freeze stability and fast recovery. Fan-assisted airflow with 100 mm all-round insulation minimizes heat gain and speeds pull-down/re-pull after door openings, maintaining a consistent -22 to -10 °C holding range across all levels.
- ✓ Low-maintenance freezer cycle. Automatic defrost with controlled heaters (evaporator only) restores coil efficiency without manual intervention, while automatic condensate evaporation keeps operation clean and reduces downtime.
- ✓ HACCP-ready temperature control. Digital thermostat with display provides precise setpoints and clear, at-a-glance readings for logging; operators can fine-tune to product and workload, ensuring compliant storage.
- ✓ Sealing, security, and serviceability. Self-closing, lockable solid door limits frost ingress and protects stock; easily replaceable magnetic gaskets preserve the seal.
- ✓ Professional build and capacity. Food-safe AISI 304 stainless steel inside/out; GN 2/1 loading with 3 adjustable shelves and approx. 700 L capacity in a 74 × 83 cm footprint (201 cm high) for high storage-per-m<sup>2</sup> in back-of-house layouts.



## PRODUCT SPECIFICATIONS

Dimensions	74 x 83 x 201 cm/h
Temperature	-22 °C to -10 °C
Volume	700 L
Rated current	3.3 A
Refrigerant/Mass	R290 / 70 g
Energy source	220 V / 50 Hz
Foaming agent	C5H10