



STAINLESS STEEL UPRIGHT REFRIGERATOR

TKSA-URS1410

STANDARD FEATURES

Double doors

- ✓ Fast pull-down, even temperature. Fan-assisted cooling circulates air uniformly across all levels, preventing warm spots and speeding recovery after door openings. Combined with 60 mm all-round insulation, it maintains a stable +2 to +8 °C hold for dependable food safety.
- ✓ Low-maintenance by design. Automatic defrost and automatic condensate evaporation eliminate routine ice removal and water pan handling, keeping performance consistent. This reduces downtime and preserves evaporator efficiency over the life of the cabinet.
- ✓ Precise, HACCP-friendly control. An adjustable digital thermostat with display provides clear setpoints and at-a-glance temperature checks for logs. Operators can fine-tune targets quickly to match product requirements and service conditions.
- ✓ Serviceability and product protection. A self-closing, lockable solid doors with easily replaceable magnetic gaskets preserves the seal, limits heat gain, and secures stock after hours.
- ✓ Professional construction and capacity. Built in AISI 304 stainless steel inside and out for hygiene and corrosion resistance. Offers GN 2/1 compatibility, 6 adjustable shelves, and 1410 L capacity in a 143 × 83 cm footprint (height 201 cm) for excellent storage per m².



PRODUCT SPECIFICATIONS

Dimensions	148 x 83 x 201 cm/h
Temperature	2 °C to 8 °C
Volume	1410 L
Rated current	2.8 A
Refrigerant/Mass	R290 / 110 g
Energy source	220 V / 50 Hz
Foaming agent	C5H10